

MCBs DX³ [6000] - 10 kA

thermal magnetic MCBs from 0.5 A to 63 A - D curve




4 079 67




4 080 33



4 080 87



4 081 43



Technical characteristics [see e-catalogue](#)

Conform to IEC 60898-1

Compatible with both prong-type and fork type supply busbars

Breaking capacity:

[6000] - IEC 60898-1 - 400 V~

10 kA - IEC 60947-2 - 400 V~

Can be equipped with DX³ signalling and remote tripping auxiliaries, motorised controls (p. 64) and add-on modules (p. 62)

Pack	Cat.Nos	Single pole 230/400 V~		Pack	Cat.Nos	3-pole 400 V~	
	D curve	Nominal rating In (A)	Number of modules		D curve	Nominal rating In (A)	Number of modules
1	4 079 62	0.5	1	1	4 080 80	0.5	3
1	4 079 63	1	1	1	4 080 81	1	3
1	4 079 64	2	1	1	4 080 82	2	3
1	4 079 65	3	1	1	4 080 83	3	3
1	4 079 66	4	1	1	4 080 84	4	3
1	4 079 67	6	1	1	4 080 85	6	3
1	4 079 69	10	1	1	4 080 87	10	3
1	4 079 70	13	1	1	4 080 88	13	3
1	4 079 71	16	1	1	4 080 89	16	3
1	4 079 72	20	1	1	4 080 90	20	3
1	4 079 73	25	1	1	4 080 91	25	3
1	4 079 74	32	1	1	4 080 92	32	3
1	4 079 75	40	1	1	4 080 93	40	3
1	4 079 76	50	1	1	4 080 94	50	3
1	4 079 77	63	1	1	4 080 95	63	3

Pack	Cat.Nos	2-pole 230/400 V~		Pack	Cat.Nos	4-pole 400 V~	
	D curve	Nominal rating In (A)	Number of modules		D curve	Nominal rating In (A)	Number of modules
1	4 080 22	0.5	2	1	4 081 43	6	4
1	4 080 23	1	2	1	4 081 45	10	4
1	4 080 24	2	2	1	4 081 46	13	4
1	4 080 25	3	2	1	4 081 47	16	4
1	4 080 26	4	2	1	4 081 48	20	4
1	4 080 27	6	2	1	4 081 49	25	4
1	4 080 29	10	2	1	4 081 50	32	4
1	4 080 30	13	2	1	4 081 51	40	4
1	4 080 31	16	2	1	4 081 52	50	4
1	4 080 32	20	2	1	4 081 53	63	4
1	4 080 33	25	2				
1	4 080 34	32	2				
1	4 080 35	40	2				
1	4 080 36	50	2				
1	4 080 37	63	2				