

Osmoz control and signalling units: illuminated heads (continued)



Technical characteristics p. 321 and see e-catalogue

Supplied with fixing ring
IP 66, IP 69K
Conform to IEC 60947-5-1

Pack	Cat.Nos	Selector switches		Positions
		With standard handle		
1	0 240 31	● Red		2 stay-put positions - 45°
5	0 240 32	● Green		
1	0 240 33	● Black		
1	0 240 35	● Red		2 stay-put positions - 45°
1	0 240 36	● Green		
1	0 240 37	● Black		
1	0 240 41	● Red		2 stay-put positions - 90°
5	0 240 42	● Green		
5	0 240 43	● Black		
1	0 240 51	● Red		3 stay-put positions - 45°
1	0 240 52	● Green		
1	0 240 53	● Black		
1	0 240 54	● Red		3 positions with spring-return from right to 0 - 45°
1	0 240 55	● Green		
1	0 240 56	● Black		
1	0 240 57	● Red		3 positions with spring-return to 0 - 45°
1	0 240 58	● Green		
1	0 240 59	● Black		
		With long handle IP 66		
1	0 240 60	● Black		2 stay-put positions - 45°
1	0 240 61	● Black		3 stay-put positions - 45°

Pack	Cat.Nos	One-piece pilot lights
		To be used without electrical block
		With integrated Led
10	0 241 20	○ White - 24 V~/=
10	0 241 21	● Red - 24 V~/=
10	0 241 22	● Green - 24 V~/=
1	0 241 23	● Blue - 24 V~/=
10	0 241 24	● Yellow - 24 V~/=
1	0 241 30	○ White - 130 V~
1	0 241 31	● Red - 130 V~
1	0 241 32	● Green - 130 V~
1	0 241 33	● Blue - 130 V~
1	0 241 34	● Yellow - 130 V~
10	0 241 40	○ White - 230 V~
10	0 241 41	● Red - 230 V~
10	0 241 42	● Green - 230 V~
1	0 241 43	● Blue - 230 V~
10	0 241 44	● Yellow - 230 V~
		For BA9S lamp (not supplied)
		Direct supply
10	0 241 00	○ Colourless
10	0 241 01	● Red
10	0 241 02	● Green
1	0 241 03	● Blue
10	0 241 04	● Yellow
10	0 241 05	○ White

		Stay-put mushroom head	
		Push-pull	
1	0 240 80	● Red - Emergency stop Ø40	
5	0 240 82	● Red - EN 418 emergency stop Ø40	
		Push-turn	
1	0 240 91	● Red - Emergency stop Ø40	
		Pilot lights	
10	0 241 60	○ White	
10	0 241 61	● Red	
10	0 241 62	● Green	
5	0 241 63	● Blue	
5	0 241 64	● Yellow	

Weatherproof cabinets, p. 261

