

# DRX™ 630 adjustable

thermal magnetic MCCBs from 320 to 630 A



# DRX™ 630 adjustable accessories



6 676 51

Technical characteristics and curves **p. 132-133**  
Dimensions and installation principle **see e-catalogue**

For switching, control, isolation and protection of low-voltage electrical lines  
Can be fitted with auxiliaries

- Supplied with:
- Screw terminals
  - Fixing screws
  - Insulating shields (2 for 3P and 3 for 4P)
- Adjustable thermal and magnetic  
Conform to IEC 60947-2

Pack	Cat.Nos		DRX 630
			Thermal adjustable from 0.8 to 1 x In Magnetic adjustable from 5 to 10 x In
	3P	4P	<b>Breaking capacity Icu 36 kA (415 V~)</b>
1	6 676 50	6 676 54	In
1	6 676 51	6 676 55	320 A
1	6 676 52	6 676 56	400 A
1	6 676 53	6 676 57	500 A
			630 A
			<b>Breaking capacity Icu 50 kA (415 V~)</b>
1	6 676 58	6 676 62	In
1	6 676 59	6 676 63	320 A
1	6 676 60	6 676 64	400 A
1	6 676 61	6 676 65	500 A
			630 A



Pack	Cat.Nos		Rotary handles
1	0 272 50		<b>Direct</b> Standard (grey)
1	0 272 51		<b>Vari-depth handle</b> Comprising: connecting rod, bracket, drilling template, mounting accessories, door locking mechanism Standard (grey)
	0 262 30		<b>Connection accessories</b>
	3P	4P	<b>Insulating shields</b> Used to isolate the connection between each pole Set of 2 pieces
1	0 262 44	0 262 45	<b>Sealable terminal shields</b> Set of 2
1	4 222 34	4 222 35	<b>IP 20 terminal cover</b> Set of two terminal covers
1	0 262 50		<b>Cage terminals</b> Set of 4 cage terminals for cables
1	0 262 51		Set of 4 high capacity cage terminals for cables
1	0 262 47		<b>Extended front terminals</b> Set of 4 extended front terminals
1	0 262 48	0 262 49	<b>Spreaders</b> Set of incoming or outgoing spreaders
1	0 263 50	0 263 51	<b>Swivel terminals</b> Set of incoming or outgoing swivel terminals
1	0 263 52	0 263 53	<b>Flat terminals</b> Set of incoming or outgoing flat terminals



DRX 250 HP and DRX 630 brochure  
**Please, consult us**



Dimensions  
**see e-catalogue**

