

Air circuit breakers DMX³ 2500 and 4000

from 800 to 4000 A



0 286 56 + 0 288 02 (p. 161)



0 286 74 + 0 288 02 (p. 161)



0 287 56 + 0 288 02 (p. 161)

Dimensions **see e-catalogue**
 Electrical characteristics **see e-catalogue**

Automatic air circuit breakers must be equipped with electronic protection unit (p. 161), imperatively ordered together for factory assembly
 Please ask for DMX³ order form
 Conform to IEC 60947-2

Pack	Cat.Nos		Fixed version	Pack	Cat.Nos		Draw-out version
			Supplied with - 4 auxiliary contacts: NO/NC - rear terminals for horizontal connection with bars - door sealing DMX³ - N 2500 Breaking capacity Icu 50 kA (415 V \sim)				Supplied with: - 4 auxiliary contacts: NO/NC - draw-out base and kit - flat rear terminals for connection with bars - door sealing DMX³ - N 2500 Breaking capacity Icu 50 kA (415 VA)
	Frame 2500				Frame 2500		
	3P	4P	In(A)		3P	4P	In(A)
1	0 286 21	0 286 31	800	1	0 287 21	0 287 31	800
1	0 286 22	0 286 32	1000	1	0 287 22	0 287 32	1000
1	0 286 23	0 286 33	1250	1	0 287 23	0 287 33	1250
1	0 286 24	0 286 34	1600	1	0 287 24	0 287 34	1600
1	0 286 25	0 286 35	2000	1	0 287 25	0 287 35	2000
1	0 286 26	0 286 36	2500	1	0 287 26	0 287 36	2500
			DMX³ - H 2500 Breaking capacity Icu 65 kA (415 V \sim)				DMX³ - H 2500 Breaking capacity Icu 65 kA (415 VA)
	Frame 2500				Frame 2500		
	3P	4P	In(A)		3P	4P	In(A)
1	0 286 41	0 286 51	800	1	0 287 41	0 287 51	800
1	0 286 42	0 286 52	1000	1	0 287 42	0 287 52	1000
1	0 286 43	0 286 53	1250	1	0 287 43	0 287 53	1250
1	0 286 44	0 286 54	1600	1	0 287 44	0 287 54	1600
1	0 286 45	0 286 55	2000	1	0 287 45	0 287 55	2000
1	0 286 46	0 286 56	2500	1	0 287 46	0 287 56	2500
			DMX³ - L 2500 Breaking capacity Icu 100 kA (415 V \sim)				DMX³ - L 2500 Breaking capacity Icu 100 kA (415 VA)
	Frame 4000				Frame 4000		
	3P	4P	In(A)		3P	4P	In(A)
1	0 286 61	0 286 71	800	1	0 287 61	0 287 71	800
1	0 286 62	0 286 72	1000	1	0 287 62	0 287 72	1000
1	0 286 63	0 286 73	1250	1	0 287 63	0 287 73	1250
1	0 286 64	0 286 74	1600	1	0 287 64	0 287 74	1600
1	0 286 65	0 286 75	2000	1	0 287 65	0 287 75	2000
1	0 286 66	0 286 76	2500	1	0 287 66	0 287 76	2500
			DMX³ - N 4000 Breaking capacity Icu 50 kA (415 V \sim)				DMX³ - N 4000 Breaking capacity Icu 50 kA (415 VA)
	Frame 4000				Frame 4000		
	3P	4P	In(A)		3P	4P	In(A)
1	0 286 27	0 286 37	3200	1	0 287 27	0 287 37	3200
1	0 286 28	0 286 38	4000	1	0 287 28	0 287 38	4000
			DMX³ - H 4000 Breaking capacity Icu 65 kA (415 V \sim)				DMX³ - H 4000 Breaking capacity Icu 65 kA (415 VA)
	Frame 4000				Frame 4000		
	3P	4P	In(A)		3P	4P	In(A)
1	0 286 47	0 286 57	3200	1	0 287 47	0 287 57	3200
1	0 286 48	0 286 58	4000	1	0 287 48	0 287 58	4000
			DMX³ - L 4000 Breaking capacity Icu 100 kA (415 V \sim)				DMX³ - L 4000 Breaking capacity Icu 100 kA (415 VA)
	Frame 4000				Frame 4000		
	3P	4P	In(A)		3P	4P	In(A)
1	0 286 67	0 286 77	3200	1	0 287 67	0 287 77	3200
1	0 286 68	0 286 78	4000	1	0 287 68	0 287 78	4000