

Other chimes



0 416 50

Pack	Cat.Nos	Electromechanical chimes																
1	0 416 50	White Dim.: 116 x 116 x 48 mm Tone level: 80 dB at 1 m 8-12 V ~ chime Compatible with non-illuminated push-button Cat.No 0 416 46 or illuminated push-buttons Cat.Nos 0 416 45/47 Use a 8 VA transformer Cat.No 4 130 91 or 0 420 25																
		1	0 416 51	127/230 V ~ chime 2 note chime - 50/60 Hz Compatible with illuminated push-button Cat.No 0 416 45														
		1	0 416 52	230 V ~ chime with transformer 50/60 Hz with built-in 8-12 V transformer Class II Compatible with non-illuminated push-button Cat.No 0 416 46 or illuminated push-buttons Cat.Nos 0 416 45/47														
10	0 420 25	Transformer - 230 V/12 V - 8 V Conform to IEC 61 558-2-8 standard Protected against short-circuits and overvoltages Wall-mounting with screws																
		<table><tr><th>Secondary tension (V)</th><th>Intensity (A)</th><th>Power (VA)</th><th colspan="3">Dimensions (mm)</th></tr><tr><th></th><th></th><th></th><th>Length</th><th>Depth</th><th>Height</th></tr><tr><td>12/8</td><td>1</td><td>12</td><td>92</td><td>56</td><td>42</td></tr></table>	Secondary tension (V)	Intensity (A)	Power (VA)	Dimensions (mm)						Length	Depth	Height	12/8	1	12	92
Secondary tension (V)	Intensity (A)	Power (VA)	Dimensions (mm)															
			Length	Depth	Height													
12/8	1	12	92	56	42													

Bells, bell pushes



0 416 46



0 416 47



0 412 43

Pack	Cat.Nos	Bell pushes
5	0 416 46	Surface-mounting White Supplied without fixing screws 24 V - 2 A bell push IP 30 - class III W Dim.: 50 x 25 x 20 mm
10	0 416 45	230 V - 2 A bell push with illuminated label holder IP 30 - class II Supplied without lamp Dim.: 70 x 35 x 24 mm
10	0 416 47	24 V - 2 A universal - bell push with label holder Weatherproof IP 44 (IK 07) - Class III W Dim.: 70 x 70 x 25 mm Can be used with any type of chimes (electronic or electromechanical)
10	0 412 21	Lido bells IP 20 - IK 04 Average acoustic output at 1 m: 80 dB at 1 m Surface-mounting with screws with levelling facilities Class II (double insulated)
1	0 412 43	230 V~ - 50/60 Hz Dim.: 95 x 61 x 33 mm With built-in transformer 230 V~ - 50/60 Hz Dim.: 135 x 88 x 48 mm Warning: take lamps out of the bell pushes

Consumption (mA)	Average acoustic output at 1 m in dB
30	80
45	80